

GRAPHICS - PROMOTIONAL

Issue date : 17/01/2011  
Date last modification : 09/12/2016**4-GL3B-07361 RI-JET 150 STATIC GLOSS WHITE BRD200****Face Material**

Gloss white plasticised static cling vinyl.

Type	Static cling vinyl	
Colour and Finish	Gloss white	
Weight	170 g/m <sup>2</sup> ±10%	ISO-536
Thickness	150 µ ±10%	ISO 534-80

**Adhesive**

This material is without adhesive.

Reference	n.a.	
Type	n.a.	
Min. Appl. Temp.	n.a.	
Service Temp.	n.a.	
Shear	n.a.	
Tack	n.a. N/25mm	FINAT FTM9
Final Adhesion	n.a. N/25mm	FINAT FTM2

**Liner**

Type	Cast coated board	
Colour and Finish	White	
Weight	200 g/m <sup>2</sup>	PP-032 - ISO 536
	±10%	
Thickness	255 µ ±10%	ISO 534
Transparency	n.a. %	DIN 53 147-64

**Applications**

For use in advertising specialties such as retail window signage and promotional displays and novelty stickers. This product is fully REACH compliant and does not contain phthalate plasticisers. It conforms to European Toy Standard EN71 part 3.

**Printing Methods**

This product gives excellent print results with UV, solvent and eco solvent ink jet printing. There are high levels of plasticiser in this type of PVC, which can lead to cosmetic imperfections and poor ink key, which is very much dependent on the type of ink used, the colour of the ink and colour density: very light coverage and light colours are most susceptible combinations for print related issues. Testing for suitability between media, printers and inks is always recommended prior to use.

**Shelf life**

6 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

