


INCREASE VISIBILITY IN LOW-LIGHT CONDITIONS, DIN 20471 CERTIFIED.

Reflective heat transfer material is thin, economical with a reflective finish. This material has a no-tack backing and is easy to cut and weed.



AVAILABLE IN

50 cm x 25 m rolls

RECOMMENDED FABRICS

- 100% cotton
- 100% polyester*
- Polyester-cotton blends
- * Test before application!

CUTTING NOTES

You should always test cut prior to any production run. Remember cutter settings will need to be adjusted as the blade ages. For optimal cutting and weeding, maintain a line thickness of at least 3 mm for lettering and logos.

APPLICATION INSTRUCTIONS

• Temperature: 150° C

• Time: 5 sec. Repressing 5 sec.

Pressure: medium
(#4-6 on Hotronix®)
Peel: warm-cold

MULTI-COLOR DESIGNS

 ${\sf CAD\text{-}CUT}^{\texttt{@}}\ {\sf Reflective}\ is\ not\ suitable\ for\ mulit-layer\ application.}$

ACCESSORIES RECOMMENDED

- Grip Cover Sheet
- Cover Sheet Non-Sticky
- EZ Weeder®

CARE INSTRUCTIONS

Machine wash up to 40° C using mild detergent. Do not use bleach. Dry at normal dryer settings on household machines. Do not dry clean. Iron only inside out.

STORAGE

Store in cool, dry area. Avoid direct heat, sunlight and humidity.

DETAILS



Flock





CAD-CUT® REFLECTIVE





