













PLOTTABLE THERMAL ADHESIVE FOR HEAT TRANSFER FOILS

CAD-CUT® Adhesive is a plottable heat activated adhesive which is needed for applying heat transfer foils.

Cut the desired design as you would cut a regular flex film, apply adhesive to textile, cover design with heat transfer foil (color side facing up) and press.

That's how easy it is to produce beautiful and shiny foil-embellished designs.



AVAILABLE IN

30 cm x 9,1 m rolls

RECOMMENDED FABRICS

- 100% cotton
- Poly-cotton blends
- Polyester blends
- 100% Polyester

CUTTING NOTES

You should always test cut prior to any production run. Remember cutter settings will need to be adjusted as the blade ages. For optimal cutting and weeding, maintain a line thickness of at least 1.5 mm for lettering and logos.

APPLICATION INSTRUCTIONS

Temperature: 150° C
Time: 10 sec.
Pressure: light-medium
(#2-6 on Hotronix®)

• Peel: hot

MULTI-COLOR DESIGNS

ACCESSORIES RECOMMENDED

- Grip Cover Sheet
- Cover Sheet Non-Sticky
- EZ Weeder®

CARE INSTRUCTIONS

Machine wash up to 30° C using mild detergent. Do not use bleach. Dry at normal dryer settings on household machines. Do not dry clean. Can be directly ironed.

STORAGE

Store in cool, dry area. Avoid direct heat, sunlight and humidity.

DETAILS





