



FEATURES / APPLICATIONS

- UV printable
- Indoor & outdoor window ads
- Removable glue
- Laminated OPP film (Additional Liner)

DATASHEET MSOWV16M

MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC
PVC		
TYPE	-	Calendered monomeric soft PVC film
THICKNESS	-	180 ± 10um / 7mil
COLOR	-	Ceramic Clear
BACK	-	Black
SHRINKAGE	-	< 0.6%
SURFACE TENSION	-	> 30dn / cm
OPACITY	-	> 99%
HOLES NO.	-	Average 130 / sq in
HOLE DIAMETER	-	1.6mm
DISTANCE BETWEEN HOLES	-	2.4mm
HOLE SPACE	-	41%
ADHESIVE		
TYPE	-	Clear solvent bases removable pressure sensitive glue
WEIGHT (G/M2)	-	30 ± 2
ADHESION TEMPERATURE	-	15 °C ~ 40 °C
PEELING FORCE	GB2792-81 China National Standard	> 4.5N / 25mm 20min
INITIAL ADHES. BALL TACK	GB4852-84	> 5# Steel Ball
HOLDING POWER	GB4854-84	> 800min
REMOVABLE DURABILITY	-	One year cleanly removable glue on clean glass surface at temperature of 23 ~ 25 °C and RH of 50 ~ 60%
LINER		
TYPE	-	Laminated OPP film (Additional Liner)
COLOR	-	White
WEIGHT	-	90g ± 5 g/m2
RELEASE FORCE	-	0.2 ± 0.1N / 25mm

INK PRINTABILITY

Solvent, Eco Solvent, UV, Latex

NOTE:

All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.