

## PRODUCT DESCRIPTION

## CONFORM 4700RLA®

A heavyweight premium grade, highly saturated paper with higher elongation, provides resistance to abrasion, moisture and delamination. Coated with a medium-low tack rubber adhesive, 4700LT RLA is designed for use with vinyl paint masks, such as RTape's ProGrade paint mask or Avery's calendared vinyl paint mask. This Conform® Series tape features RLA® Release Liner Adhesion for improved adhesion to paper or film release liners.. RTape RLA™ Premasks anchor themselves to the release liner for superior lay flat to prevent tunneling and edge curling of stacked or rolled graphics. During storage of graphics 4700LT RLA maintains the specified adhesion level to the vinyl or printed graphic.

Adhesive	Rubber-based
Color	White/Translucent
Caliper, facestock	127 microns (5.0 mils)
Caliper, facestock + adhesive	152 microns (6.0 mils)
Adhesion to Stainless Steel	9 – 11 N/100mm (8 – 10 oz.)
Tensile	332 N/100mm (19lb./in)
Elongation	12%
Tear Resistance (grams)	70–80
Shelf life Stored at 22°C (72°F)/ 50-55 % RH	1 year

## FEATURES & BENEFITS

- Exceptional choice for use on extra -large markings, such as OEM, RV and marine paint stencils.
- The medium-low tack, latex adhesive provides for easy removal from the paint mask stencil following the transfer of the graphics, without pulling off the vinyl mask from the substrate.
- Features RLA® Release Liner Adhesion formula, which allows the tape to stick to large areas of exposed release liners.
- If the 4700LT RLA Conform® Series tape needs to be torn, it tears easily with no annoying stringy adhesive.

## APPLICATIONS

- Heavyweight Application Tape for Vinyl Paint Mask Stencils

**Important Notice:** All RTape products are subject to continuous quality control throughout the manufacturing process and are warranted to be free from manufacturing defects. RTape stands behind its products and will replace or credit any defective material. Because R Tape products are used for a variety of applications, the purchaser is responsible for determining the suitability and performance of this product for their specific purpose, prior to use and the purchaser shall assume all risks regarding such use.