

APLITAPE 4885**HEAVYWEIGHT PAPER APPLICATION TAPE****TECH DATA SHEET**

White translucent heavyweight saturated paper with ultra high tack rubber adhesive designed for very small lettering and graphics and hard-to-lift films. Exceptional resistance to abrasion and moisture.

PHYSICAL SPECIFICATIONS

Adhesive	Rubber-based
Color	White/Translucent
Caliper <i>facestock</i>	127- 140 microns (5-5.5mils)
Caliper <i>facestock + adhesive</i>	152 microns (6.0 mils)
Adhesion to Steel*	22+ N/100mm (20+oz.)
Tensile	332 N/100mm (19lb./in)
Elongation	12%
Tear Resistance	70-80
Shelf Life**	1 year
Base	{tag_base}

APPLICATIONS

- Application tape for small Graphics, thermal die cut graphics.
- Designed for highly textured surfaces and four color UV clear coats.

PRINTER PROFILES

Printer profiles are available on rtape.com.

WARRANTY

Tapes are only warranted to be free of defect in workmanship or materials at time of shipment. Manufacturer will replace or credit any material manufacturer deems defective. No acceptance or responsibility for loss, damage, or expense, implies or otherwise, shall be assumed by seller or manufacturer. User assumes all risk and liability herewith.

FEATURES

- Transfer of hard-to-lift textured vinyls, etched glass vinyls, and small thermal die cut graphics.
- Very small lettering and fine detail plotter-cut graphics.

* Adhesion PSTC-101, 1 min dwell on stainless steel

** Stored at 22 OC / 50-55% RH

RESPONSIVE
RELIABLE
RESOURCEFUL