



Quality and performance in an affordably priced application tape.

ApliTape™ is the original RTape application tape. It has all of the great features of RTape's popular Conform® series, but without the RLA® Release Liner Adhesion additive. Available in standard and heavyweight paper grades, in a variety of tack levels.

4050 Medium Tack

Standard grade saturated paper application tape, coated with a medium tack rubber adhesive.

4075 High Tack

Standard grade saturated paper application tape, coated with a high tack rubber adhesive.

Applications

General Purpose Sign Applications
Screen Printing
Digital Printing

Product Information

Factory cut, razor slit rolls
Rubber adhesive
Available in a variety of tack levels
No adhesive build-up on stored graphics
Works in either wet or dry applications
No adhesive balls, gapping between layers or crushed edges



TECHNICAL DATA ▶

Physical Properties		4050	4075
Color		White/Translucent	White/Translucent
Adhesive		Rubber-Based	Rubber-Based
Caliper	Facestock	4.0 - 4.5 mil (100-113 μ)	4.0 - 4.5 mil (100-113 μ)
	Facestock + Adhesive	5.0 - 5.5 mil (125-138 μ)	5.0 - 5.5 mil (125-138 μ)
Tack Level		Medium	High
Adhesion to Steel*		13 - 15 N/100 mm (12 - 14 oz)	18 - 20 N/100 mm (16 - 18 oz)
Die-Cut Graphics Size		Mid-Sized	Mid-Sized
Tensile		297 N/100 mm (17 lb/in)	297 N/100 mm (17 lb/in)
Elongation		3-4%	3-4%
Tear Resistance		50	50
Shelf Life		1 Year	1 Year

* TEST METHOD: PSTC-101



WARRANTY Tapes are only warranted to be free of defects in workmanship or materials at time of shipment. Nekoosa will replace or credit any material deemed to be defective. No acceptance or responsibility for loss, damage, or expense, implied or otherwise, shall be assumed by the seller or manufacturer. The end user assumes all risk and liability.