



Always lays flat, with no edge curling, wrinkling, or tunneling.

Conform® is the original application tape with RLA® Release Liner Adhesion. With RLA, Conform sticks to slick release liners, so tapes do not “dog ear” and stick together. Graphics stay neater and cleaner, even when they’re rolled.

**4075RLA** High Tack *Most popular!*

Standard weight paper application tape with a high tack rubber adhesive. Perfect for small to mid-sized pre-spaced vinyls and printed graphics.

**4076RLA** Very High Tack

Standard weight paper application tape, coated with a slightly higher tack rubber adhesive. Perfect for small-sized cut graphics and hard-to-lift vinyls.

**4050RLA** Medium Tack

Standard weight paper application tape with a medium tack rubber adhesive. Perfect for medium to large-sized, prespaced vinyl and printed graphics.

**4078RLA** Medium Tack

Standard weight paper application tape with a medium tack rubber adhesive. Recommended for applying wall graphics, textured and frosted vinyl.

### Applications

General Purpose Sign Applications  
Decals  
Banners  
Wall Graphics

### Product Information


RLA® Release Liner Adhesion  
Lays flat with no tunneling or edge curling  
Factory cut, razor slit rolls  
No adhesive balls, gapping between layers or crushed edges  
Tears cleanly – no stringy, legging adhesive  
Multiple roll widths available  
No adhesive build-up on stored graphics  
Works in either wet or dry applications



## TECHNICAL DATA ▶

Physical Properties		4078RLA	4050RLA	4075RLA	4076RLA
<b>Adhesive</b>	Rubber-Based				
<b>Color</b>	Off White/Translucent				
<b>Tensile</b>	297 N/100 mm (17lb/in)				
<b>Elongation</b>	3-4%				
<b>Tear Resistance</b>	50				
<b>Shelf Life</b>	1 Year				
<b>Caliper</b>	Facestock	3.0 mil	3.0 mil	3.0 mil	3.0 mil
	Facestock + Adhesive	4.1 mil	4.2 mil	4.2 mil	4.3 mil
<b>Tack Level</b>		Medium	Medium	High	Very High Tack
<b>Adhesion to Steel*</b>		9 - 11 N/100 mm (7.5 - 8 oz)	13 - 15 N/100 mm (12 - 14 oz)	18 - 20 N/100 mm (16 - 18 oz)	19 - 21 N/100 mm (17 - 19 oz)

\* TEST METHOD: PSTC-101



**WARRANTY** Tapes are only warranted to be free of defects in workmanship or materials at time of shipment. Nekoosa will replace or credit any material deemed to be defective. No acceptance or responsibility for loss, damage, or expense, implied or otherwise, shall be assumed by the seller or manufacturer. The end user assumes all risk and liability.