



A NEKOOSA BRAND



GXP-525

Technical Data

Product Description – A low tack paper application tape for vinyl graphics used in sign making and surface protection. The product consists of a self-wound, standard grade saturated backing coated with a specially formulated latex pressure sensitive adhesive.

Product Characteristics

Construction		
Backing	White translucent latex saturated paper	
Adhesive	Water based natural latex	
Total Thickness	4 mil (nominal)	
Performance		
Tensile Strength (pli)		
MD	20	
Elongation (%)	2.4	
Average Adhesion (oz/in)		
180° Peel @ time of manufacture		
PSTC#4 bright annealed stainless steel		10.0

The physical properties listed above are typical values and are not to be considered as specifications. Our suggestions for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for their internal use. Nekoosa assumes no liability for claims beyond those outlined within our Limited Warranty, which includes replacement value of Nekoosa product proven defective. For full disclosure of the Limited Liability Warranty, please contact your Nekoosa representative.

Typical Uses - Economical premask for for large vinyl graphics and large format digital prints. Excellent choice for one-piece decals > 12" in one dimension.



MAN PRINT & SIGN B.V.
G.G. Schipperstraat 26
1483 GE, De Rijp

T: 0031-(0)299-393390
sales@manprint-sign.nl
www.manprint-sign.nl