



A NEKOOSA BRAND



GXP-550

Technical Data

Product Description – A medium tack paper application tape for vinyl graphics used in sign making and surface protection. The product consists of a self-wound, standard grade saturated backing coated with a specially formulated latex pressure sensitive adhesive.

Product Characteristics

Construction

Backing	White translucent latex saturated paper
Adhesive	Water based natural latex
Total Thickness	4 mil (nominal)

Performance

Tensile Strength (pli)	
MD	20
Elongation (%)	2.4

Adhesion (oz/in)

180° Peel @ time of manufacture	
PSTC#4 bright annealed stainless steel	4.0 - 18.0

The physical properties listed above are typical values and are not to be considered as specifications. Our suggestions for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for their internal use. Nekoosa assumes no liability for claims beyond those outlined within our Limited Warranty, which includes replacement value of Nekoosa product proven defective. For full disclosure of the Limited Liability Warranty, please contact your Nekoosa representative.

Typical Uses - Excellent for medium and large plotter and die-cut graphics. Works well with pre-spaced lettering 2-12", small one piece decals and mid-sized line striping.



MAN PRINT & SIGN B.V.
G.G. Schipperstraat 26
1483 GE, De Rijp

T: 0031-(0)299-393390
sales@manprint-sign.nl
www.manprint-sign.nl