



ATR SERIES

METALLISED FILM

Choose the LLumar® ATR Series for a custom, slightly reflective look that's great at fighting heat. Hard-working LLumar ATR harnesses metal's mirror-like quality to reflect heat away, enhance interior comfort, and help protect you and your vehicle's upholstery from the sun's harmful rays.

- Great heat rejection
- More than 99% UV protection*
- Enhanced style
- Increased privacy for passengers and belongings
- Variety of shades from light to dark
- Charcoal colour matches factory-installed privacy glass
- Scratch-resistant coating helps protect against damage
- Enhanced protection from shattered glass
- Manufacturer's 10 year limited warranty**

* Wavelengths 300-380nm

** Certain restrictions apply; see a dealer for details.

ATR SERIES

ATR 05 CH SR HPR (Charcoal)

Performance Data

% Visible Light Transmission	5
% Total Solar Energy Rejection	61
% IR Energy Rejection (IRER) (wavelengths 780-2500nm)	22
% Selective IR Rejection (SIRR) (wavelengths 780-2500nm)	68
% Ultraviolet Protection (wavelengths 300-380nm)	>99
% Glare Reduction	94
% Visible Light Reflection (exterior)	6

ATR SERIES

ATR 15 CH SR HPR (Charcoal)

Performance Data

% Visible Light Transmission	18
% Total Solar Energy Rejection	48
% IR Energy Rejection (IRER) (wavelengths 780-2500nm)	38
% Selective IR Rejection (SIRR) (wavelengths 780-2500nm)	51
% Ultraviolet Protection (wavelengths 300-380nm)	>99
% Glare Reduction	80
% Visible Light Reflection (exterior)	5

ATR SERIES

ATR 20 CH SR HPR (Charcoal)

Performance Data

% Visible Light Transmission	25
% Total Solar Energy Rejection	47
% IR Energy Rejection (IRER) (wavelengths 780-2500nm)	39
% Selective IR Rejection (SIRR) (wavelengths 780-2500nm)	52
% Ultraviolet Protection (wavelengths 300-380nm)	>99
% Glare Reduction	71
% Visible Light Reflection (exterior)	6

ATR SERIES

ATR 35 CH SR HPR (Charcoal)

Performance Data

% Visible Light Transmission	37
% Total Solar Energy Rejection	44
% IR Energy Rejection (IRER) (wavelengths 780-2500nm)	40
% Selective IR Rejection (SIRR) (wavelengths 780-2500nm)	53
% Ultraviolet Protection (wavelengths 300-380nm)	>99
% Glare Reduction	59
% Visible Light Reflection (exterior)	8

ATR SERIES

ATR 50 CH SR HPR (Charcoal)

Performance Data

% Visible Light Transmission	53
% Total Solar Energy Rejection	35
% IR Energy Rejection (IRER) (wavelengths 780-2500nm)	29
% Selective IR Rejection (SIRR) (wavelengths 780-2500nm)	37
% Ultraviolet Protection (wavelengths 300-380nm)	>99
% Glare Reduction	40
% Visible Light Reflection (exterior)	9