



IRX SERIES

INFRARED-REJECTING CERAMIC FILM

Transform your vehicle inside and out with the LLumar® IRX Series. It features advanced, infrared-blocking nanoceramic technology so you'll feel cooler and more comfortable, even on the hottest days. LLumar IRX also delivers everything else you'd want in a premium film: head-turning style, easy connectivity, UV protection and a reduction in annoying glare.

- Our best, IR-blocking heat rejection
- Advanced technology won't interfere with electronics
- More than 99% UV protection*
- Enhanced style
- Increased privacy for passengers and belongings
- Variety of shades from light to dark
- Charcoal colour matches factory-installed privacy glass
- Scratch-resistant coating helps protect against damage
- Enhanced protection from shattered glass
- Manufacturer's lifetime limited warranty**

* Wavelengths 300-380nm

** Certain restrictions apply; see a dealer for details.

IRX SERIES

IRX 05 CH SR HPR (Charcoal)

Performance Data*

% Visible Light Transmission	5
% Total Solar Energy Rejection	62
% IR Energy Rejection (IRER) (wavelengths 780-2500nm)	59
% Selective IR Rejection (SIRR) (wavelengths 780-2500nm)	85
% Ultraviolet Protection (wavelengths 300-380nm)	>99
% Glare Reduction	94
% Visible Light Reflection (exterior)	5

* Based on data obtained during product development and is subject to change.

IRX SERIES

IRX 15 CH SR HPR (Charcoal)

Performance Data*

% Visible Light Transmission	20
% Total Solar Energy Rejection	59
% IR Energy Rejection (IRER) (wavelengths 780-2500nm)	61
% Selective IR Rejection (SIRR) (wavelengths 780-2500nm)	88
% Ultraviolet Protection (wavelengths 300-380nm)	>99
% Glare Reduction	77
% Visible Light Reflection (exterior)	5

* Based on data obtained during product development and is subject to change.

IRX SERIES

IRX 35 CH SR HPR (Charcoal)

Performance Data*

% Visible Light Transmission	38
% Total Solar Energy Rejection	54
% IR Energy Rejection (IRER) (wavelengths 780-2500nm)	60
% Selective IR Rejection (SIRR) (wavelengths 780-2500nm)	87
% Ultraviolet Protection (wavelengths 300-380nm)	>99
% Glare Reduction	56
% Visible Light Reflection (exterior)	6

* Based on data obtained during product development and is subject to change.

IRX SERIES

IRX 50 CH SR HPR (Charcoal)

Performance Data*

% Visible Light Transmission	53
% Total Solar Energy Rejection	49
% IR Energy Rejection (IRER) (wavelengths 780-2500nm)	60
% Selective IR Rejection (SIRR) (wavelengths 780-2500nm)	87
% Ultraviolet Protection (wavelengths 300-380nm)	>99
% Glare Reduction	40
% Visible Light Reflection (exterior)	7

* Based on data obtained during product development and is subject to change.