



VALOR

PAINT PROTECTION FILM

PROTECTION
**ONE
AND
DONE**

COMBINING THE BEST OF BOTH WORLDS IN
PAINT PROTECTION, USING OEM-TRUSTED
TETRASHIELD™ TECHNOLOGY



Redefining confidence, LLumar Valor Paint Protection Film brings together coveted features of both paint protection film and ceramic coating into one truly remarkable and durable product. With a new and improved super hydrophobic top coat***, self-healing LLumar Valor helps deliver effortless cleaning and has serious fighting power for even more resistance to damage.



SELF-HEALING PROTECTION

Self-heals surface scratches with heat, offering protection against rocks, road debris, winter salt and sand



EASY CLEAN SUPER HYDROPHOBIC TOP COAT***

OEM-trusted Tetrashield™ technology; super hydrophobic*** for less water and dirt build-up



DISCOLOURATION & STAIN RESISTANCE

Protection against discoloration and excellent stain resistance so dirt, oil, tar and bugs don't stand a chance



CLARITY & SHINE

Smooth clear finish with exceptional gloss, free of orange peel texture



RESISTANCE FROM NATURE'S TOUGHEST HAZARDS

Serious fighting power with up to 25% more resistance* against bird droppings, acid rain and tree sap



MANUFACTURER'S 12 YEAR LIMITED WARRANTY**

Our strongest PPF warranty, providing confidence for miles

EASTMAN

LLumar.com | LLumar.co.uk

* Compared to other top brands. ** Certain restrictions apply. ***The durability and level of hydrophobic property can be influenced by environmental conditions and other variables beyond Manufacturer's control (e.g., road treatment chemicals and cleaning substances/frequency). ©2022 Eastman Performance Films, LLC. All rights reserved. No liability is accepted for errors. 04/22.



VALOR

PAINT PROTECTION FILM



PHYSICAL PROPERTY	STANDARD TEST METHOD	PERFORMANCE
Chemical Resistance	ASTM D7244/ D6279 Isopropyl Alcohol	No Detrimental Effect (after 100 cycles)
Chemical Resistance	ASTM D7244/ D6279 MEK	No Detrimental Effect (after 100 cycles)
Weathering	ASTM D7869	No Detrimental Effect (after 5000hrs)
Rock Chip Resistance	SAE J400/ ASTM D3170	Pass
Thickness Range		7-8mil

All statements, technical information and recommendations herein are based on tests the manufacturer believes are reliable. The manufacturer does not warrant or guarantee the accuracy or completeness of this information.

EASTMAN

LLumar.com | LLumar.co.uk

* Compared to other top brands. ** Certain restrictions apply. ***The durability and level of hydrophobic property can be influenced by environmental conditions and other variables beyond Manufacturer's control (e.g., road treatment chemicals and cleaning substances/frequency). ©2022 Eastman Performance Films, LLC. All rights reserved. No liability is accepted for errors. 04/22.